



DTE 2/12

- Designed for the protection of data and communication lines against longitudinal and transverse surge effects.
- Contains both 1st and 2nd stage of protection.
- Suitable for use in industrial applications, especially in low-voltage ESS, FDAS systems and also in measurement and control systems.

| Type | | DTE 2/12 |
|------------------------------------------------------------------------------------------------|-------------|---------------------------|
| Testing category according to IEC 61643-21:2000 and EN 61643-21:2001 | | C1, C2, C3, D1 |
| Number of pairs | | 2 |
| Connector type | | Screw terminals |
| Rated operating DC voltage | U_N | 0 ÷ 12 V |
| Maximum continuous operating voltage DC | U_C | 14.4 V |
| Rated load current | I_L | 0.1 A |
| Maximum discharge current (8/20) | I_{max} | 10 kA |
| C2 Nominal discharge current (8/20) | I_n | 1 kA |
| C2 Voltage protection level at I_n | U_p | < 28 V |
| C3 Voltage protection level at 1 kV/μs | U_p | < 18 V |
| D1 Impulse discharge current (10/350) line/PE | I_{imp} | 2.5 kA |
| D1 Total impulse discharge current (10/350) | I_{Total} | 5 kA |
| Response time | t_A | < 30 ns |
| Data rate | | 1 Mbit/s |
| Bandwidth | B | 0 ÷ 1 MHz |
| Series impedance per line | | 2.2 Ω |
| Parasitic capacitance | C | < 1.5 nF |
| Lightning protection zone | | LPZ 0-1, LPZ 1-2, LPZ 2-3 |
| Housing material | | Polyamid PA6, UL94 V-0 |
| Degree of protection | | IP20 |
| Operating temperature | θ | -40 ÷ 70 °C |
| Clamp fastening range (solid conductor) | | 0.2 ÷ 2.5 mm ² |
| Tightening moment | | 0,5 Nm |
| Installation | | On DIN rail 35 mm |
| Modular width | | 1 TE |
| Operating position | | Any |
| Remote signalling | | No |
| Modular design | | No |
| Designed according to standards | | |
| Requirements and test methods for SPDs connected to telecommunications and signalling networks | | IEC 61643-21:2000 |

Application standards

| | | |
|------------------------------|--|----------------|
| Protection against lightning | | IEC 62305:2010 |
|------------------------------|--|----------------|

Ordering, packaging and additional data

| | | |
|----------------------------------|---|----------------------|
| Mass | m | 56 g |
| Mass (including the packaging) | m | 67 g |
| Packaging dimensions (H x W x D) | | 26 x 98 x 73 mm |
| Packaging value | V | 0.19 dm ³ |
| Customs tariff no. | | 85363010 |
| EAN code | | 8590681423028 |
| Art. number | | 42 302 |



The link in the QR code leads to the online presentation of the **DTE 2/12**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit www.hakel.com



Internal diagram

