







## **HDT2/6C Module**

 Removable modules for the protection of data and communication lines against longitudinal and transverse surge effects.

| Туре   |                | HDT2/6C Module       |
|--|----------------|----------------------|
| Rated operating DC voltage   | $U_N$          | 0 ÷ 6 V              |
| Maximum continuous operating voltage DC  | U <sub>C</sub> | 7.2 V                |
| Spare module for   |                | 56 022, 56 022/NV    |
| Designed according to standards  |                |                      |
| Requirements and test methods for SPDs connected to telecommunications and signalling networks |                | IEC 61643-21:2000    |
| Safety of Flammability of Plastic Materials  |                | UL 94                |
| Application standards  |                |                      |
| Protection against lightning   |                | IEC 62305:2010       |
| Ordering, packaging and additional data  |                |                      |
| Mass   | m              | 23 g                 |
| Mass (including the packaging)   | m              | 34 g                 |
| Packaging dimensions (H x W x D)   |                | 26 x 98 x 73 mm      |
| Packaging value  | V              | 0.19 dm <sup>3</sup> |
| Customs tariff no.   |                | 85363010             |
| EAN code   |                | 8590681168127        |
| Art. number  |                | 56 022/M             |



**The link in the QR code** leads to the online presentation of the **HDT2/6C Module**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit **www.hakel.com** 

