

KO-6GN (F/M)

KO* is an innovated coaxial high-frequency protection range **designed for protection of equipment connected to an aerial system by means of coaxial cables**. Special gas discharge tubes **with maximum discharge current I_{max} (8/20) = 10kA** (or 20 kA in case of KO-5GN) ensure a reliable protection of the receiving and transmitting systems even against a lightning stroke nearby. Hakel company offers a wide range of coaxial protectors for various connector types and transmission power grades enabling usage in many applications. **These coaxial protectors are recommended for use in the Lightning Protection Zones Concept at the boundaries of LPZ 0_{A(B)} -1 and higher according to EN 62305.**

PARAMETERS

Typ		KO-6GN (F/M)
Connector type		N connector
Maximum continuous operating voltage	U_c	135 V
Rated load current	I_L	5 A
D1 Max. lightning impulse current I_{imp} (10/350 μ s)	I_{imp}	1 kA
C2 Max. discharge current (8/20)	I_{max}	10 kA
C2 Nominal discharge current I_n (8/20)	I_n	5 kA
C3 Voltage protection level at 1 kV/ μ S	U_p	< 500 V
Frequency range		0-5,8 GHz
Max. transmission power capacity		50 W
Insertion loss		< 0,2 dB
Return loss		> 20 dB
Characteristic impedance		50 Ω
Category tested acc. to IEC 61643-21:2000		C1, C2, C3, D1
Article number		
KO-6GN (F/M)		55 026



KO-6GN (F/M)



Product image

